


## RVEN-70 : 7/8 Lobe 3.5 Stage



### Dimensions

Bit to Stabilizer Center	A	27 in
Bit to Bend, Fixed	B	48 in
Bit to Top Sub	C	382 in
Body OD, Slick	D	7.0 in
Body OD, Stabilizer	D	7.5 in
Pad Radius, Fixed	E	3.75 in
Bottom Connection	4-1/2 REG Box 6-5/8 REG Box 4-1/2 IF Pin	
Top Connection	4-1/2 IF Box 4-1/2 XH Box	
Top Sub Float Bore	4R	

### Recommended Operating Limits

Max WOB	117,000 lbf
Max Overpull, Backream	169,000 lbf
Max Overpull, Re-Run	325,000 lbf
Max Overpull, POOH	630,000 lbf

### Predicted Build Rates (Fixed) – Degrees/100ft


Bend Setting	Slick Hole Size			Stabilized Hole Size		
	8 1/2	8 3/4	9 7/8	8 1/2	8 3/4	9 7/8
<b>Deg</b>						
<b>0.78</b>	2.1	1.4	1.9	4.6	4.7	5.2
<b>1.15</b>	4.4	3.6	0.4	6.7	6.8	7.4
<b>1.50</b>	6.5	5.8	2.5	8.7	8.8	9.4
<b>1.75</b>	8.0	7.3	4.0	10.1	10.2	10.8
<b>1.83</b>	8.5	7.8	4.5	10.6	10.7	11.2
<b>2.00</b>	9.5	8.8	5.5	11.5	11.7	12.2
<b>2.12</b>	10.3	9.5	6.3	12.2	12.4	12.9
<b>2.25*</b>	11.1	10.3	7.1	13.0	13.1	13.6
<b>2.38*</b>	11.8	11.1	7.8	13.7	13.8	14.4
<b>2.50*</b>	12.6	11.8	8.6	14.4	14.5	15.1

\*Bend Setting not recommended for Rotary Drilling

### Performance Details

	HP
Max Diff Pressure	880 psi
Max Torque	15,000 lbf-ft
Stall Torque	22,500 lbf-ft
Rotation	0.150 rev/gal
Flow Range	300-600 gpm
Speed Range	45-90 rpm

### Theoretical Performance Curve



Performance curves based on testing at 70°F. Actual field performance may vary with field operation conditions.